







- 1.LCD: TFT, TRANSMISSIVE, NORMALLY WHITE
- 2.Top: -20°C~70°C, Tst:-30°C~80°C
- 3.VIEWING DIRECTION: 6 O'CLOCK (GRAYSCALE INVERSION)
- 4.B/L:CONSTANT CURRENT IF=160mA, VF=9.8V(TYP)
- 5.TOLERANCE FOR NOT ASSIGNED ±0.3 mm
- 6.THIS PRODUCT CONFORM WITH THE STANDARD OF ROHS
- 7.THE MINIMUM BENDABLE RADIUS(INNER) OF THE FPC IS 1.0mm
- 8.COMPONENT AREA AND SOLDERING AREA CAN NOT BENDING
- 9.CN1 : 6705K-E40N-00L(E&T) OR EQUIVALENT



T/P PIN	
PIN NO.	PIN ASSIGNMENT
1	X1
2	Y1
3	X2
4	Y2



DETAIL "B"

		DETAIL "B"
REV	DATE	MODEL: UMSH-9392MD-5T(REVE)
0	Mar.13.19'	TITLE: OUTLINE DRAWING
1		DESIGN: H.F. Kuo
2		CHECK: Titan Lo
3		APPROVAL: CKT Chen